

RansNet UA-800X

4G/5G | Wi-Fi 6 | IoT | SD-Branch

A Compact 5G Wireless Router
Optimized for Mobility and IoT Applications



RansNet UA-800X is an industrial grade wireless router, designed to connect IoT/mobility devices over 4G/5G wireless network, together with RansNet Software-Defined-Branch (SD-Branch) technologies and central orchestration platform, to offer an end-to-end secure communication solution for mobility, IoT and Industrial 4.0 applications.

Equipped with dedicated 5G module, the UA-800X provides reliable and high-speed Wireless Wide-Area-Network (WWAN) backhaul as primary or backup to a fixed line, to reliably connect robotics, vehicles or IoT devices to central application servers, at highest possible speed and lowest latency. This global version model supports all mainstream providers frequency bands, and automatically connects to 5G NSA/SA or LTE, whichever is available with best performance. Its "Gigabit LTE" (Cat16) carrier aggregation capability produces much higher speed than typical 4G routers, making it an ideal choice to transit from 4G to 5G era, with absolute investment protection.

The Qualcomm-powered appliance comes with Gigabit Ethernet WAN & LAN ports and 802.11ax Wi-Fi, producing up to 1Gbps firewall throughput and up to 800Mbps VPN throughput (IPSec AES-256). Installed with RansNet OS, the UA-800X supports full SD-Branch features, to guarantee security and end-to-end application performance, at minimum operational overheads.

The UA-800X has compact lightweight design with metal casing, easy to fit into any enclosures or moving vehicles, and is able to sustain working in harsh conditions, particularly useful for empowering mobility and industrial 4.0/IoT use cases.

Key features

- Dedicated 5G module. Support 5G NSA/SA and LTE, auto switch/failover
- Worldwide 5G NR, LTE-A, UMTS/HSPA(+) and GSM/GPRS/EDGE coverage
- Integrated Wi-Fi 6, GPS, Bluetooth and Z-Wave* for LAN/IoT devices
- Gigabit Ethernet WAN for fixed line and LAN for local extension
- Multi-WAN for link balancing and auto failover between fixed and 4G/5G
- Stateful firewall for perimeter defense
- Network Access Control for endpoint security and identity management
- VPN for data encryption and transport security over the air
- Dynamic routing and traffic steering for application performance
- Built-in MQTT broker* for IoT support
- Zero-Touch-Provisioning for easy deployment
- SD-WAN orchestration for central configuration and monitoring




5G NR Sub-6 Bands
NSA & SA



DL: LTE Cat 16
UL: LTE Cat 18



802.11b/g/n/ax
Wi-Fi 6



Gigabit Ethernet
WAN and LAN



Multi-constellation
GNSS



MQTT Broker *



Stateful Firewall



Multi-protocol VPN
(SSL/IPSec/GRE)



Software-Defined
Wide Area Network

Hardware Specifications

Processor	Qualcomm Quad-Core (IPQ6010)
Memory (Flash, RAM)	64MB, 1GB RAM
Firewall throughput	1Gbps
VPN throughput	800Mbps (IPSec with AES-256 encryption)
Concurrent devices	Up to 200
Concurrent connections	Up to 500,000
Multi-WAN	YES (Fixed line + 5G/4G + Wi-Fi as WAN)
Gigabit Ethernet	1 x WAN, 2 x LAN (All ports are configurable as either WAN or LAN)
Console	1 x USB-C, Baud Rate 115200bps

5G/LTE/Wi-Fi Specifications

5G Modem	Quectel RM5xx Series
SIM Card Slot	Single SIM
5G/NR Bands	5G NSA: n1/3/5/7/8/20/28/38/40/41/71/75/76/77/78 5G SA: n1/3/5/7/8/20/28/38/40/41/71/75/76/77/78
5G/NR peak data rate (theoretical)	NSA data rate: DL 3.4Gbps, UL 550Mbps SA data rate: DL 2.4Gbps, UL 900Mbps
4G/LTE Bands	FDD: B1/2/3/4/5/7/8/12/13/14/17/18/19/20/25/26/28/29/30/32/66/71 TDD: B34/38/39/40/41/42/43/48
4G/LTE peak data rate (theoretical)	DL 1.6 Gbps (Cat 19) UL 200 Mbps (Cat 18)
Wi-Fi Standard	802.11b/g/n/ax, 2 x 2 MU-MIMO OFDMA AP and STA mode (Wi-Fi as WAN)
Wi-Fi peak data rate (theoretical)	Up to 1.49Gbps
Antenna Connectors	4x SMA Cellular Connectors 2x RP-SMA Wi-Fi Antenna Connectors

Physical Specification

Power Input Options	Power Port: 12V – 56V DC (Screw) USB-C: 5V 4A Type C Terminal Block: 12V – 56V DC
Power Consumption	< 12W
Design form factor	Compact form factor
Dimensions (WxDxH, mm)	135 x 150 x 30
Weight	< 800g
Humidity	15% – 95% (non-condensing)
Operating temperature	-30°C to 80°C
Certification	FCC, CE, E-Mark *
Package Content	1 x UA-800X 2 x Wi-Fi Antennas 1 x 24V/2A 3-Pin Power Supply (5G Antennas are sold separately)
Warranty	1-Year Limited Warranty

* Under development

Network and Security Features

IPv4, IPv6	✓
DHCP services (client and server)	✓
MQTT broker (mosquitto)*	✓
VLAN/Trunking (IEEE 802.1q)	✓
Ethernet bridging (IEEE 802.1d)	✓
Bonding/EtherChannel/LACP (IEEE 802.3ad)	✓
High Availability (VRRP)	✓
Static and Dynamic routing (OSPF/BGP)	✓
Policy-Based Routing (PBR)	✓
SNMP, NetFlow, OpenFlow, Syslog, iperf3	✓
DNS filtering	✓
Stateful Firewall, NAT, SNAT, DNAT, Port Forwarding	✓
Access logging for security audit and compliance	✓
SD-Branch Orchestration and Monitoring	✓
Cloud or on-premise gateway deployment	✓
Cloud or on-premise orchestration (mfusion)	✓
Zero-touch provisioning	✓
Multi-VPN protocols: WireGuard, SSLVPN, IPSec, L2TPv3, GRE, DMVPN	✓
Multiple VPN modes: L2VPN, L3VPN, Remote Access	✓
Multiple VPN topologies: star or mesh	✓
Ethernet over VPN (VXLAN with BGP EVPN)	✓
Auto SD-WAN VPN and routing provisioning	✓
Template based configuration and monitoring	✓
Application-based Traffic-shaping	✓
Performance-based traffic steering	✓
Dynamic VLAN assignment based on device or user identity (NAC)	✓
Super-tenant multi-role based dashboard access	✓
Real-time device and SD-WAN topology update	✓
Alert on device/link failures or thresholds	✓
Extensive dashboard customization	✓
Customizable scheduled reporting	✓